



0.752 ±0.001 DIA.
0.750 DEEP
BUSHED HOLE FOR
TRUNNION PIN
BOTH SIDES

* STANDARD LOCATION, OTHER LOCATIONS WILL BE USED
ON UNITS THAT ARE NOT HORIZONTALLY MOUNTED.

DIMENSIONS FOR STANDARD STROKES	
STROKE	A
6.00	10.18
12.00	16.18
18.00	24.68

NOTES:

1. OTHER SPECIAL MOUNTINGS AND ARRANGEMENTS ARE AVAILABLE.
 2. UNIT MAY BE MOUNTED IN ANY POSITION, HOWEVER THE MOUNTING POSITION MUST BE IDENTIFIED WHEN ORDERING.
 3. NOT DESIGNED FOR CONTINUOUS OPERATION OF MOTOR.
 4. SHOWN WITH 1/3 HP ELECTRIC MOTOR.
 5. CONTACT THE KERRY CO., INC. FOR SPECIAL ROD ENDS AND MOUNTING CONFIGURATIONS WHEN REQUIRED.
 6. DIMENSIONS ARE NOT CERTIFIED FOR CONSTRUCTION.
- SEE ACCESSORIES PAGE FOR MOUNTING BRACKETS, ETC.