



DIMENSIONS FOR STANDARD STROKES	
STROKE	A
12.00	19.12
18.00	25.12
24.00	31.12
36.00	46.72
48.00	62.32

DIMENSIONS B, C, D, E, F AND LEAD DIA. TEFEC MOTORS						
HP	B	C	D	E	F	FRAME LEAD DIA.
2	32.68	6.62	5.73	4.62	3.76	56C 0.88
3	32.12	6.62	5.73	4.62	3.76	56C 0.88
5	35.37	8.50	6.87	5.76	4.26	184TC 1.09
7.5	37.56	10.25	9.22	7.37	N/A	213TC 1.38
10	38.06	10.28	9.22	7.37	N/A	213TC 1.38

\* STANDARD LOCATION, OTHER LOCATIONS WILL BE USED ON UNITS THAT ARE NOT HORIZONTALLY MOUNTED.

- NOTES:
1. OTHER SPECIAL MOUNTINGS AND ARRANGEMENTS ARE AVAILABLE.
  2. UNIT MAY BE MOUNTED IN ANY POSITION, HOWEVER THE MOUNTING POSITION MUST BE IDENTIFIED WHEN ORDERING.
  3. NOT DESIGNED FOR CONTINUOUS OPERATION OF MOTOR.
  4. CONTACT THE KERRY CO., INC. FOR SPECIAL ROD ENDS AND MOUNTING CONFIGURATIONS WHEN REQUIRED.
  5. UNIT ALSO AVAILABLE WITH 2.000 DIA. ROD FOR SPECIAL APPLICATIONS AND LONGER STROKES.
  6. DIMENSIONS ARE NOT CERTIFIED FOR CONSTRUCTION.

SEE ACCESSORIES PAGE FOR MOUNTING BRACKETS, ETC.

THE KERRY CO., INC. M-SERIES (1.75) ELECTRO-HYDRAULIC LINEAR ACTUATOR