



DIMENSIONS FOR STANDARD STROKES	
STROKE	A
6.00	9.72
12.00	15.72
18.00	21.72
20.00	23.72
24.00	30.22
30.00	36.72
36.00	43.22

- NOTES:**
1. OTHER SPECIAL MOUNTINGS AND ARRANGEMENTS ARE AVAILABLE.
 2. UNIT MAY BE MOUNTED IN ANY POSITION, HOWEVER THE MOUNTING POSITION MUST BE IDENTIFIED WHEN ORDERING.
 3. NOT DESIGNED FOR CONTINUOUS OPERATION OF MOTOR.
 4. CONTACT THE KERRY CO., INC. FOR SPECIAL ROD ENDS AND MOUNTING CONFIGURATIONS WHEN REQUIRED.
 5. UNIT AVAILABLE WITH UP TO 2 HP DEPENDING UPON FORCE AND ROD SPEED REQUIRED.
 6. DIMENSIONS ARE NOT CERTIFIED FOR CONSTRUCTION.

* STANDARD LOCATION, OTHER LOCATIONS WILL BE USED ON UNITS THAT ARE NOT HORIZONTALLY MOUNTED.

SEE ACCESSORIES PAGE FOR MOUNTING BRACKETS, ETC.