



* STANDARD LOCATION, OTHER LOCATIONS WILL BE USED ON UNITS THAT ARE NOT HORIZONTALLY MOUNTED.

DIMENSIONS FOR STANDARD STROKES

STROKE	A	B
6.00	13.18	32.68
12.00	19.18	32.68
18.00	25.18	32.68
20.00	27.18	34.68
24.00	33.68	34.68
30.00	40.18	34.68
36.00	48.68	34.68

- NOTES:**
- OTHER SPECIAL MOUNTINGS AND ARRANGEMENTS ARE AVAILABLE.
 - UNIT MAY BE MOUNTED IN ANY POSITION, HOWEVER THE MOUNTING POSITION MUST BE IDENTIFIED WHEN ORDERING.
 - NOT DESIGNED FOR CONTINUOUS OPERATION OF MOTOR.
 - CONTACT THE KERRY CO., INC. FOR SPECIAL ROD ENDS AND MOUNTING CONFIGURATIONS WHEN REQUIRED.
 - DIMENSIONS ARE NOT CERTIFIED FOR CONSTRUCTION.

SEE ACCESSORIES PAGE FOR MOUNTING BRACKETS, ETC.

NOTE:
THE ABOVE UNIT IS SHOWN WITH A STANDARD 2.000 BORE X 1.000 ROD CYLINDER SECTION. JE STYLE UNITS ARE AVAILABLE WITH LARGER BORE AND STROKE CYLINDER SECTION. CONTACT THE MANUFACTURER OR YOUR LOCAL SALE REPRESENTATIVE FOR FURTHER INFORMATION.