



JUNCTION BOX

0.752 ±0.001 DIA.
 0.750 DEEP
 BUSHED HOLE FOR
 TRUNNION PIN
 BOTH SIDES

DISTANCE FACE TO FACE OF TRUNNION BUSHINGS

* STANDARD LOCATION, OTHER LOCATIONS WILL BE USED ON UNITS THAT ARE NOT HORIZONTALLY MOUNTED.

DIMENSIONS FOR
 STANDARD STROKES

STROKE	A
6.00	10.18
12.00	16.18
18.00	24.68

NOTES:

1. OTHER SPECIAL MOUNTINGS AND ARRANGEMENTS ARE AVAILABLE.
2. UNIT MAY BE MOUNTED IN ANY POSITION, HOWEVER THE MOUNTING POSITION MUST BE IDENTIFIED WHEN ORDERING.
3. NOT DESIGNED FOR CONTINUOUS OPERATION OF MOTOR.
4. SHOWN WITH 1/3 HP ELECTRIC MOTOR.
5. CONTACT THE KERRY CO., INC. FOR SPECIAL ROD ENDS AND MOUNTING CONFIGURATIONS WHEN REQUIRED.
6. DIMENSIONS ARE NOT CERTIFIED FOR CONSTRUCTION.

SEE ACCESSORIES PAGE FOR MOUNTING BRACKETS, ETC.

THE KERRY CO., INC. K-SERIES ELECTRO-HYDRAULIC LINEAR ACTUATOR