



MODEL NO.	SIZE	ROTATION	A	B	C	D	E	F	G	H	J	K	L	M	N
KR-	750	180°	6.31	2.98	3.00	1.31	0.8735	1/2"	1/2"	2.63	2.38	3/16"	3.38	0.625	0.187
KR-	1500	90°	6.31				0.8750	1"	3/4"			5/8"	3.38	0.627	0.188
KR-	3000	180°	8.10	3.94	4.50	1.88	1.248	1/2"	1/2"	3.00	3.63	3/8"	3.82	0.875	0.187
KR-	6000	90°	8.10				1.250	1"	3/4"			5/8"	3.82	0.877	0.188
KR-	12500	180°	11.24	5.25	6.88	3.38	2.248	1 1/2"	1 1/2"	4.75	4.88	3/4"	6.75	1.500	0.375
KR-	25000	90°	11.24				2.250	2"	1 1/2"			13/16"	6.75	1.503	0.376
KR-	50000	180°	17.19						3/8"						
KR-	100000	90°	17.19						3/8"						
KR-	250000	180°	24.60	8.63	11.5	4.50	2.998	3/4"	3/4"	7.38	9.13	1 1/4"	9.63	2.750	0.625
KR-	500000	90°	24.60				3.000	3"	3/8"			1 5/8"	9.63	2.752	0.626
KR-	1250000	180°	33.39												
KR-	2500000	90°	33.39												
KR-	5000000	180°	45.58	14.5	16.5	7.50	4.998	1 1/2"	1 1/2"	13.0	13.5	1 1/4"	15.88	3.750	0.750
KR-	10000000	90°	45.58				5.000	1 3/4"	1 3/4"			1 3/4"	15.88	3.754	0.751
KR-	20000000	180°	67.57												

- NOTES:
1. Standard mount face and bolt pattern shown. Optional mounting available.
 2. Standard male shaft shown for each model. Option shafts available.
 3. Fail safe, limit switches, position transmitters, visual indicators and manual pumps available.
 4. Please contact The Kerry Company for any special applications.
 5. Standard units are not designed for continuous operation of motor.
 6. Dimensions are not certified for construction.
 7. Horsepower rating of motors depend on torque and speed required.

THE KERRY CO., INC. KRE-SERIES ELECTRO-HYDRAULIC ROTARY ACTUATOR