



MODEL	REV.	REV. DATE	REV. DESCRIPTION	A	B	C	D	E	F	G	H	J	K	L	M	N
KRM-750	1	1800	3000	6.31	1.196	2.38	3.00	1.31	0.835	1.7	2.63	2.38	3.38	0.52	0.87	0.88
KRM-1500	2	1800	3000	6.31	1.196	2.38	3.00	1.31	0.835	1.7	2.63	2.38	3.38	0.52	0.87	0.88
KRM-3000	1	1800	3000	8.49	1.24	3.94	4.50	1.88	1.248	1.7	3.00	3.63	3.87	0.875	0.88	0.88
KRM-4000	2	1800	3000	8.49	1.24	3.94	4.50	1.88	1.248	1.7	3.00	3.63	3.87	0.875	0.88	0.88
KRM-12500	1	1800	3000	11.24	1.52	5.25	6.38	2.248	1.51	2.0	4.75	4.88	6.25	1.500	0.375	0.375
KRM-25000	2	1800	3000	11.24	1.52	5.25	6.38	2.248	1.51	2.0	4.75	4.88	6.25	1.500	0.375	0.375
KRM-62500	1	1800	3000	24.60	3.83	11.5	14.50	2.998	3.47	3.8	12.8	9.13	9.63	2.250	0.625	0.625
KRM-125000	2	1800	3000	24.60	3.83	11.5	14.50	2.998	3.47	3.8	12.8	9.13	9.63	2.250	0.625	0.625
KRM-250000	1	1800	3000	34.59	4.58	14.5	16.5	7.50	4.998	5.0	13.0	13.5	11.4	1.588	0.750	0.750
KRM-500000	2	1800	3000	34.59	4.58	14.5	16.5	7.50	4.998	5.0	13.0	13.5	11.4	1.588	0.750	0.750

- NOTES:
- Standard mount face and bolt pattern shown.
  - Optional mounting available.
  - Standard male shaft shown for each model.
  - Option shafts available.
  - Fail safe, limit switches, position transmitters, visual indicators and manual pumps available.
  - Please contact The Kerry Company for any special applications.
  - Standard units are not designed for continuous operation of motor.
  - Dimensions are not certified for construction.
  - Horsepower rating of motors depend on torque and speed required.

DIMENSIONS C, D, E, F AND LEAD DIA. TEFC MOTORS									
HP	P	Q	R	S	T MAX	FRAME	LEAD DIA.		
2	6.62	5.73	4.62	3.76	49.37	56C	0.88		
3	6.62	5.73	4.62	3.76	49.37	56C	0.88		
5	8.50	6.87	5.76	4.26	50.68	184TC	1.09		
7.5	10.25	9.22	7.37	N/A	52.68	213TC	1.38		
10	10.28	9.22	7.37	N/A	54.68	213TC	1.38		

THE KERRY CO., INC. KRM-SERIES ELECTRO-HYDRAULIC ROTARY ACTUATOR